

APD 275 C

Cummins
Aksa
D+' &'



Manufacturer		Cummins		
Model		6 LTAA8,9-G2		
		% \$\$\$' "# "		
		&(\$\$\$' "		
		0&&Z\$<DQ		
	L	8,900		
	"	114 X 145		
		16,6:1		
	fl # 7	"# "	1500	
	fl 7	L	27,60	
		L	41,10	
AbsorbedAirDischargeReSourceKey.Text	' # "	15,20		
	' # "	475,00		
	' # "	38,00		
	° C	470,00		
		24 V d.c.		
	Load	%\$\$i	'+) i) \$i
	# "	53,00	39,00	27,00

		Aksa
		AK4200
	Hz	50
	"	250,00
7cg'		0,80
		3
	fl 7	400/230

		fl 7		fl 7	
	"	"	"	"	L
APD 275 C	2050,00	2600,00	1250,00	1680,00	473,00
		fl 7		fl 7	
	"	"	"	"	L
ASM 6A	2600.00	3650	1310	2040	473

APD 275 C

Cummins
Aksa
D+' &''

AKSA POWER DIESEL



SZUTEST

GC - \$\$\$%

2000/14/EC

&\$\$\$#/(#

z) \$' z' \$z 'D:

	"	"	"	"	Amp
400/230	275,00	220,00	250,00	200,00	361,00

fPGL' 'GC') & ' ' z&('GC' \$(*"

Standard Specifications

- Water cooled, Diesel engine
- Radiator with mechanical fan
- Protective grille for fan and rotating parts
- Electric starter and charge alternator
- Starting battery (with lead acid) including rack and cables
- Base frame design incorporates an integral fuel tank and anti-vibration isolators
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel belows supplied separately
- Static battery charger
- Manual for use and installation.

! " fl " t

ALTERNATOR

! "

TRANSFER SWITCH

! "

APD 275 C

Cummins
Aksa D+ &



5GA *5!



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 Base frame -fuel tank.
- 9 Lifting Points.
- 10 sound proofing materials.

	"	1310
fl "L	"	3650
fl "L	"	2040
	L	473