

Technical Engine Data

16V4000G63

Water charge air cooling (external);

50 Hz - 1.500/min

fuel consumption optimized



Operating method	Four stroke Diesel	Flywheel housing flange	SAE 00
Combustion system	Direct Injection	Flywheel interface	21
Charging method	Exhaust turbo charger and Water charge air cooling (external);	Starter ring-gear teeth no.	182
Bore / Stroke	170 / 210 mm	Injection system	Common Rail System with electronically controlled high-pressure injection through single injection pumps
Displacement, total	76.3 Liter	Control / Monitoring	Electronic engine management system "ADEC"
Number of cylinders	16	Number of turbo chargers	4
Cylinder configuration	V - 90°	Number of intercooler	1
Compression ratio	16.5 : 1		
Direction of rotation (viewed from flywheel side)	left		

MTU-Application group				3D (ICFN)	3B (ICXN)
Power (ISO 3046)		kW	A	2185	1965
Mean piston speed		m/s	A	10.5	10.5
Mean effective pressure		bar	A	22.9	20.6
Engine weight (Engine in basic execution)	dry	kg	R	7700	7700
	wet	kg	R	-	-
Dimensions (Engine only)	length	mm	R	3001	3001
	height	mm	R	1660	1660
	width	mm	R	2154	2154
Consumption					
Specific fuel consumption (be) (Tolerance +5% according to ISO 3046/1)	100% CP	g/kWh	G	195	191
	75% CP	g/kWh	R	193	193
	50% CP	g/kWh	R	198	203
Lube oil consumption (after run-in)			R	-	-
Capacity					
Engine oil capacity, initial filling (standard oil system)	total	Liter	R	300	300
	Oil pan capacity, dipstick mark min.	Liter	L	210	210
	Oil pan capacity, dipstick mark max.	Liter	L	240	240
Engine coolant capacity (without cooling equipment)		Liter	R	175	175
Intercooler coolant capacity		Liter	R	50	50
Heat dissipation					
Engine coolant dissipation	100% load	kW	R	800	730
Charge-air heat dissipation	100% load	kW	R	410	320
Radiation and convection heat, engine		kW	R	90	90
Starter system					
Electrical Starter (make Delco)					
Starter, rated voltage		V	R	24	24
Starter, rated power		kW	R	-	-
Starter, power requirement max.		A	R	-	-
Starter, power requirement at firing speed		A	R	-	-
Recommended battery capacity	Lead-acid	Ah/20h	R	450	450
	NiCd	Ah/5h	R	240	240
Firing speed		1/min	R	80 - 120	80 - 120
Coolant pre-heating					
Preheating temperature (min.)		°C	R	32	32
Heater performance		kW	R	9	9

Technical Engine Data

16V4000G63

Water charge air cooling (external);

50 Hz - 1.500/min

fuel consumption optimized



MTU-Application group			3D (ICFN)	3B (ICXN)
Coolant system, Engine coolant circuit				
Coolant temperature (at engine outlet to cooling equipment)	°C	A	100	100
Coolant temperature after engine, alarm	°C	R	102	102
Coolant temperature after engine, shutdown	°C	L	104	104
Coolant antifreeze content, max. permissible	%	L	50	50
Cooling equipment: coolant flow rate	m ³ /h	A	68.5	68.5
Coolant pump: inlet pressure, min.	bar	L	0.2	0.2
Coolant pump: inlet pressure, max.	bar	L	1.5	1.5
Pressure loss in off-engine cooling system, max. permissible	bar	L	0.7	0.7
Cooling equipment: height above engine max. permissible	m	L	15	15
Cooling equipment: design pressure	bar	A	2.5	2.5
Coolant system, Charge-air coolant circuit				
Coolant temperature before intercooler (engine inlet)	°C	A	55	55
Coolant antifreeze content, max. permissible	%	L	50	50
Cooling equipment: coolant flow rate	m ³ /h	A	30	30
Pressure loss in off-engine cooling system max. permissible	bar	L	0.7	0.7
Cooling equipment: height above engine max. permissible	m	L	15	15
Cooling equipment: design pressure max. permissible	bar	A	2.5	2.5
Combustion air				
Combustion air volume flow	m ³ /s	R	2.6	2.3
Intake air depression	mbar	A	15	15
Intake air depression new filter limit value	mbar	L	50	50
Fuel system				
Fuel supply flow, max.	l/min	R	17	14
Fuel temperature, max.	°C	L	55	55
Fuel pressure at supply connection on engine, max. admissible	bar	L	1.5	1.5
Fuel pressure at supply connection on engine, min. admissible	bar	L	-0.1	-0.1
Exhaust system				
Exhaust volume flow	m ³ /s	R	6.6	5.8
Exhaust temperature after turbocharger	°C	R	490	485
Exhaust backpressure limit value	mbar	L	85	85
General operating data				
Recommended minimum continuous load	%	R	20	20
Engine mass moment of inertia, with standard flywheel	kgm ²	R	23.1	23.1
Noise emission				
(Free-field sound pressure level, 1m distance)				
Engine surface noise	dB(A)	R	106	109
Exhaust noise, unsilenced	dB(A)	R	115	113

A = Design value; G = Guaranteed value; R = Guideline value

L = Limit value, up to which the engine can be operated w/o change

- = Data not available; * = Estimated or projected values

Reference conditions

	Standard	Power available up to
Intake air temperature	25°C	40°C
Site altitude above sea level	100 m	400 m

MTU Friedrichshafen GmbH
 Maybachplatz 1
 88045 Friedrichshafen/Germany
 Phone: (07541) 90 70 60
 Fax: (07541) 90 70 84

E-Mail: powergen@mtu-online.com
 Internet: www.mtu-friedrichshafen.com