



For illustrative purposes only

**Дизельная электростанция 1000 кВт**

- 1- Industrial diesel engine in genset version with certificate of origin
- 2- Industrial brushless alternator with AVR
- 3- Compact steel baseframe and fuel tank (retention basin optional)
- 4- Industrial silencer and coupling flange
- 5- Electrical panel mounted on board the unit with digital control device installed in metal box
- 6- Compact for easy handling and use
- 7- Test report, manuals and electrical drawings supplied
- 8- World wide after sales service and technical support

**Further details on the technical data sheet**

Мощность	
<b>Continuous power (PRP)</b>	<b>1280.0 (kVA)</b>
<b>Continuous power (PRP)</b>	<b>1024.0 (kW)</b>
<b>Stand-by power (LTP)</b>	<b>1400.0 (kVA)</b>
<b>Stand-by power (LTP)</b>	<b>1120.0 (kW)</b>
<b>Power factor</b>	<b>0.8</b>

**Voltage**

Frequency (Hz)	50 Hz
Voltage (V)	400 V

**Dimensions and noise level**

Width	2200 mm
Length	5500 mm
Height	2400 mm
Weight	11100 kg
Sound pressure 7 m.	0.0 dBA

**Data references**

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0,850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

**P.R.P. Prime Power-Continuous power at variable load:** The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer. according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.  
**L.T.P. Limited-time running power-Limited power:** The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

Двигатель	
Engine brand	CUMMINS
Engine model	KTA50-G3
Cylinders	16
Speed	1500 r.p.m.
Cubic capacity	50.30 l
Air intake	Turbocharged
Standard voltage	24 Vdc
Optional voltage	Vdc
Sae	0-18
BMEP	1744 kPa
Cooling	Water

**Engine power**

Flywheel P.R.P. Power	1097.0 kW
Flywheel Stand-by Power	1227.0 kW

**Fuel consumption**

Fuel Cons. at 100% (L.T.P.)	293.0 l/h
Fuel Cons. at 100% (P.R.P.)	261.0 l/h
Fuel Cons. at 75% (P.R.P.)	199.0 l/h
Fuel Cons. at 50% (P.R.P.)	139.0 l/h
Fuel Cons. at 25% (P.R.P.)	76.0 l/h

**Speed regulation**

Electronic regulator	Standard
Precision class	G2

**Engine dimensions and liquids**

Oil quantity	177.0 l
Engine Antifreeze capacity	161.0 l
Radiator standard	IM50

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.



# POWERFULL - C 1250 U



Gruppi Elettrogeni - Generating Sets  
 ГЕНЕРАТОРЫ ЭЛЕКТРИЧЕСТВА - مجموعة المولدات  
 Stromaggregate - Groupes Électrogènes - Grupos Electrógenos

## Heat from engine

Heat from radiator	775.0 kW
Heat from exhaust	845.0 kW
Heat from radiation	150.0 kW

## Exhaust data

Exhaust temperature	525 °C
Cooling air flow	1818.00 m <sup>3</sup> /min
Combustion air flow	104.80 m <sup>3</sup> /min
Exhaust gas flow	240.70 m <sup>3</sup> /min

## Emissions

TA Luft	Not available
TA Luft/2	Not available
EPA	Not available
Stage	Not available

## Alternator

Alternator brand	MECC ALTE
Alternator model	ECO43-2LN/4
P.R.P. Power	1300.0 kVA
L.T.P. Power	1420.0 kVA

## Alternator wirings

Connection	Parallel star
Phases	Trifase + Neutro
Winding	12 terminals 800 V
Terminal Number	12 nr.

## Alternator protection

IP Protection	23
---------------	----

## Voltage regulator

Electronic regulator	DER-1
Precision	1.0 ± %

## Baseframe

Model	ST60
Standard tank	0 l
Optional tank	0 l
Oversized tank*	l

## Canopy & Silencer

Canopy model	SENZA COFANO
Silencer model	MS 45
Silencer outlet diameter	219.0 mm

## Available control panels



The **GUARD EVOLUTION** device, in MANUAL or AUTOMATIC version, is designed and manufactured by Visa S.p.A. for the command, control and protection of the generating set. Main characteristics are: clear communication via a large backlit display screen; generating set event analysis through sophisticated algorithms; complete engine and electrical parameters; possibility of integrating additional modules and programme extensions; customisation for dealers (optional).

## Optional control panels



**Guard Touch** MANUAL OR AUTOMATIC is the new revolutionary controller with touch screen, researched and developed by Visa S.p.A., which will be standard supply on our gensets. From a technical and operational viewpoint, the new device is different from its predecessors, but still maintains Visa's main characteristic: MODULARITY! Guard Touch is a versatile controller able to satisfy the myriad of requests from the end-user, from manual function to totally automatic management.

## Options

Each genset model has a wide range of accessories and customised equipment choices; standard equipment and optional accessories are described in the technical data sheet. Contact our sales office for further information and details.

