

N67 SM1

121 kW@1500 rpm

138 kW@1800 rpm

Specifications

Thermodynamic cycle	Diesel 4 stroke, D.I.		
Air intake	TC		
Arrangement	6, in line		
Bore x Stroke	mm	104 x 132	
Total displacement	l	6.7	
Valves per cylinder	2		
Injection system	mechanical		
Speed governor	mechanical		
Cooling system	liquid (water + 50% Paraflu11)		
Flywheel housing/flywheel	type	SAE3 / 11" 1/2	
Flywheel rotation	CCW		
Lube oil specifications	ACEA E3-E5		
Lube oil consumption	<0.1% of fuel consumption		
Fuel specifications	EN 590		
Oil and filters intervals for replacement	hours	600	
Fuel consumption at:	rpm	1500	1800
	100% load l/h (g/kWh)	28.8 (212.5)	33.9 (216.3)
	80% load l/h (g/kWh)	23.2 (214.0)	27.5 (219.4)
	50% load l/h (g/kWh)	14.6 (216.3) 1	8.3 (233.2)
Coolant capacity: engine only	l	~10.5	
	engine+radiator	l	~40.5
ATB (without canopy)	°C	51	
No remote cooling radiator allowed			
Lube oil total system capacity including pipes, filters etc.	l	~17.2	
Electrical system	12Vcc		
Starting batteries: recommended capacity	Ah	1x100	
Discharge current (EN 50342)	A	800	
Cold starting: without air preheating	°C	-15	
	with air preheating	°C	-25

Performances

Ratings ¹		1500 rpm		1800 rpm	
		PRIME	STAND-BY	PRIME	STAND-BY
Rated Output ²	kWm	110	121	126	138

1) Ratings in accordance with ISO 8528. For duty at temperature over 40°C and/or altitude over 1000 meters must be considered a power derating factor. Contact the FPT sales organization.

2) Net power at flywheel available after 50 hours running with a ±3% tolerance.

PRIME POWER: The prime power is the maximum power available with varying loads for an unlimited number of hours. The average power output during a 24h period of operation must not exceed 80% of the declared prime power between the prescribed maintenance intervals and at standard environmental conditions. A 10% overload is permissible for 1 hour every 12 hours of operation.

STAND-BY POWER: The stand-by power is the maximum power available for a period of 500 hours/year with a mean load factor of 90% of the declared stand-by power. No kind of overloads is permissible for this use.

CONTINUOUS POWER: Contact the FPT sales organization.

Standard configuration

FPT engine N67 SM1 equipped with:

- Mounted radiator
- Mounted belt driven pusher fan
- Fan guard
- Mounted air filter with replaceable cartridges
- Fuel filter
- Primary fuel filter/water separator
- Replaceable oil filter
- Front engine mounting brackets
- Flywheel housing SAE3 and flywheel 11" 1/2
- Re-directable exhaust gas elbow
- Recircled oil breather system
- Oil dipstick
- HWT and LOP sensors
- 12Vdc electrical system
- User's handbook

THE ENGINE IS SUPPLIED WITHOUT LIQUIDS

Optional equipment:

On request the engine can be supplied with:

- Oil drain pump
- Oil drain valve
- 120/230 Volt water jacket heater
- WT and OP sensors for gauges
- Low water level sensor
- Turbo and exhaust gas guards
- Exhaust gas flexible joint
- 24Vdc electrical system
- Front radiator guard
- Electronic speed governor

Overall dimensions:

