

Дизельная электростанция Green Power GP 1380 SM/P-A

1500 rpm - 50 Hz
 1800 rpm - 60 Hz

PERKINS

3^{ph}

Trifase
 Three phase
 Triphasé
 Trifásico



Insonorizzato
 Soundproof
 Insonorisé
 Insonorizado



Raffreddato ad acqua
 Water cooled
 Refroidi à eau
 Refrigerado por agua



Motore Diesel
 Engine Diesel
 Moteur Diesel
 Motor Diesel

Perkins



Model: supersilenced 70dB(A)±3 at 7mt

Engine/alternator monoblock unit coupled through flexi-disc couplings, installed on a welded steel baseframe, complete with antivibration mountings.

Soundproof enclosure with doors made of 20/10 sheet steel, soundproof material, internal silencer, steel handles and hinges, internal fuel tank cap, lifting hook, powder painting.

EQUIPMENT SPECIFICATION (ISO 8528/1)		50Hz
Standby power at cosfi 0.8	1385 kVA	
Prime power at cosfi 0.8	1253 kVA	
Standby power at cosfi 0.8	1108 kW	
Prime power at cosfi 0.8	1003 kW	
Voltage available to the terminals	400/230 V	
Integrated fuel tank	670 lt	
Lead acid batteries	24V220Ah	
Dimensions (mm)	7000x2270x2550	
Weight (Kg)	13300	

ENGINE		50Hz
Brand and model	PERKINS 4012-46 TWG2A	
Electronic governor	ISO 3046	
Max power	1546 Hp	
R.P.M.	1500	
Cylinders	12 a V	
Displacement	45842 cc	
Fuel consumption at 75% of load	255 L/h	

ALTERNATOR		50Hz
Brand and model	MARELLI MJB 400 LB4 (*)	
Synchronous with electronic governor voltage	± 0,5%	



Green Power Systems srl

Loc. Maiano s/n - 61028 Caprazzino di Sassocorvaro (PU)
Tel. +39 0722 726411 / Fax +39 0722 720092
www.greenpowergen.com / info@greenpowergen.com

●○● MADE IN ITALY



Pole	4	
Stator/rotator insulation	H	
Protection level	IP23	
Continuous power	1300 kVA	